

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

MODELS:

YR280-AP-161

280 lb Ice Machine

Standard Features

- Up to 283 lb production ice machine (per 24 hrs)
- Built-in storage capacity of 88 lb (under counters)
- Durable stainless steel exterior
- Slanted blue plastic bin door
- Ice scoop included
- Height includes leg levelers
- Air cooled condenser
- · Removable air filter
- Power switch accessible without panel removal
- For freestanding or built-in applications
- Requires use of a drain
- NSF and ETL listed
- Ice dimension: 3/8"x 7/8" x 7/8"
- Includes 3M water filter system standard
- NEMA 5-15P plug standard

Maintenance and cleaning are not covered under warranty

All Atosa Ice machines should have the included 3M water filter system & cartridge installed. Recommended 3M cartridge replacement is recommended every 6 months. (may vary based on water quality)

- 1. Don't forget to leave the unit some room to breathe!
- 2. Please clean the condenser frequently to give the unit more fresh air.





Inlet hose





Drain hose

Ice scooper







2 YEAR PARTS AND LABOR WARRANTY 5 YEAR COMPRESSOR PART WARRANTY











REV. 05/24




ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com www.atosa.com | www.atosausa.com California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

SPECIFICATIONS

Model	Туре	Refrigerant	Voltage (V/Hz/Ph)	Rated Current (A)	Power(W)	kWh/100 lbs Ice	Ice-making Capacity (lbs/hr)	Leg (inch)	Exterior Dimensions (inch)	Gross Weight (lbs)
YR280-AP-161	Cube ice	R290	115/60/1	7.2	704	5.97	283/24	6	23 ^{1/2} ×28 ^{1/2} ×38 ^{3/5}	187

PLAN VIEW



Model	Water Inlet	Water Outlet	Bin Drain		
YR140-AP-161	3/8" "Slip" style connector / Accepts 3/8" OD Tubing	3/4" Hose Barb / Accepts 3/4" Rubber Hose (hose clamp needed)	Incorporated in Water Outlet		
YR280-AP-161	3/8" "Slip" style connector / Accepts 3/8" OD Tubing	3/4" Hose Barb / Accepts 3/4" Rubber Hose (hose clamp needed)	Incorporated in Water Outlet		
YR450-AP-161	3/8" "Slip" style connector /	3/4" Hose Barb / Accepts 3/4"	3/4" Hose Barb / Accepts 3/4"		
	Accepts 3/8" OD Tubing	Rubber Hose (hose clamp needed)	Rubber Hose (hose clamp needed)		
YR450S-AP-161	3/8" "Slip" style connector /	3/4" Hose Barb / Accepts 3/4"	3/4" Hose Barb / Accepts 3/4"		
	Accepts 3/8" OD Tubing	Rubber Hose (hose clamp needed)	Rubber Hose (hose clamp needed)		
YR800-AP-261	1/4" "Slip" style connector /	3/4" Hose Barb / Accepts 3/4"	3/4" Hose Barb / Accepts 3/4"		
	Accepts 1/4" OD Tubing	Rubber Hose (hose clamp needed)	Rubber Hose (hose clamp needed)		
HD350-AP-161	3/8" "Slip" style connector /	3/4" Hose Barb / Accepts 3/4"	3/4" Hose Barb / Accepts 3/4"		
	Accepts 3/8" OD Tubing	Rubber Hose (hose clamp needed)	Rubber Hose (hose clamp needed)		

Atosa International www.atosa.com

Atosa USA www.atosausa.com

NEMA 15A/125V